



SPECIFICATIONS

屏幕尺寸	26.5"(67.31cm)
显示区域 (mm)	590.42(H) x 333.72(V)
曲面屏幕	Flat
面板类型	QD-OLED
最佳分辨率	2560x1440 (WQHD)
点距 (H x V)	0.2292(H) x 0.2292(V)
屏幕比例	16:9
屏幕亮度	250 (Typ.)
对比度	1500000:1 (Typ.)
信号频率	96.24~580.32 KHz(H) / 45~360.9 Hz(V)
激活范围	48~360Hz
刷新率	360Hz
响应时间	0.03ms (GtG)
动态刷新率技术	AMD FreeSync™ Premium Pro
HDR支持	DisplayHDR True Black 400
显示接口	1 x DisplayPort 1.4a 2 x HDMI™ 2.1 (WQHD@360Hz) 1 x Type-c (DP alt.) w/PD 90W
USB 接口	2 x USB 2.0 Type-A 1 x USB 2.0 Type-B
音频接口	1 x Headphone-out
可视角度	178° (H) / 178° (V)
音频接口	1x Earphone out
动态对比度	100000000:1
尺寸 (W x D x H)	610 x 242 x 422 mm 610 x 69 x 356 mm (without stand)
包装尺寸 (W x D x H)	WW carton: 810 x 185 x 500 mm Outer: 828 x 200 x 525mm
表面处理	Anti-Reflection
显示色彩	1.07B ,10 bits
防盗锁	Yes
VESA 支架	100 x 100 mm
电源适配器规格	Power Cable
电源输入	100~240V, 50/60Hz
调节角度 (倾斜)	-5° ~ 20°
调节角度 (旋转)	-30° ~ 30°
中心轴旋转	-90° ~ 90°
调节范围 (高度)	0 ~ 110 mm

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



360Hz High Refresh Rate

Experience smooth gaming with a blazing fast refresh rate, that gives you the upper hand in fast-moving games.



Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.




Gaming Intelligence APP

Customize and set the ultimate monitor modes with keyboard & mouse in a very easy way. Easily activate useful function in game and take advantages.



Type-C 90W PD

Built-in a USB Type-C connection with 90W power delivery allows you to effortlessly connect to and charge your devices.




Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

PIP / PBP 分屏	N/A
窄边框设计	Yes
接口分辨率	Display Port: 2560 x 1440 (Up to 360Hz) HDMI 2.1: 2560 x 1440 (Up to 360Hz) Type C(DP alt.): 2560 x 1440 (Up to 360Hz) and 90W PD charging *Adobe RGB, DCI-P3 and sRGB follow CIE1976 Standard
重量	8.3 / 10.9 kg
Adobe RGB / DCI-P3 / sRGB	98% / 99% / 138%
Warranty	3 years (including panel burn-in)

CONNECTIONS



1. Earphone out
2. 2 x HDMI™ (2.1)
3. Display Port (1.4a)
4. USB Type-C (PD 90W)
5. USB 2.0 Type-B
6. 2 x USB 2.0 Type-A
7. 5-way Joystick Navigator
8. AC Power Jack
9. Kensington lock