



SPECIFICATIONS

| | |
|------------------|---|
| 屏幕尺寸 | 34.18" (86.82cm) |
| 显示区域 (mm) | 800.06(H)x337.06(V) |
| 曲面屏幕 | 1800R |
| 面板类型 | QD-OLED |
| 最佳分辨率 | 3440 x 1440 (UWQHD) |
| 点距 (H x V) | 0.2315(H)x0.2315(V) |
| 屏幕比例 | 21:9 |
| 屏幕亮度 | SDR:250 nits HDR:450 nits (Typ.) (True Black 400 with 10% APL) 1000 nits (Typ.) (Peak 1000 with 3% APL) |
| 对比度 | 1500000:1 |
| 信号频率 | 30~390 KHz(H) / 48~240 Hz(V) |
| 激活范围 | 48~240Hz |
| 刷新率 | 240Hz |
| 响应时间 | 0.03ms (GTG) |
| 动态刷新率技术 | Adaptive-Sync |
| HDR支持 | DisplayHDR True Black 400 |
| 显示接口 | 1x Display Port 1.4a 2x HDMI™ 2.1(UWQHD@240Hz) 1x USB 2.0 Type-C (DP alt.) w/ 98W PD |
| USB 接口 | 2x USB 2.0 Type-A 1x USB 2.0 Type-B |
| 音频接口 | 1 x Headphone-out |
| 可视角度 | 178° (H) / 178° (V) |
| 音频接口 | 1x Earphone out |
| 动态对比度 | N/A |
| 尺寸 (W x D x H) | 812 x 318 x 427mm 812 x 130 x 361mm (without stand) |
| 包装尺寸 (W X D X H) | WW carton: 1000*233*513mm Outer: 1015*248*536mm |
| 表面处理 | Anti-Reflection |
| 显示色彩 | 1.07B ,10 bits |
| 防盗锁 | Yes |
| VESA 支架 | 100 x 100 mm |
| 电源适配器规格 | Power Cable |
| 电源输入 | 100~240V, 50/60Hz |
| 调节角度 (倾斜) | -5° ~ 20° |
| 调节角度 (旋转) | -30° ~ 30° |

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming.

240Hz Extremely High Refresh Rate



Experience smooth gaming with a blazing fast 240Hz refresh rate, that gives you the upper hand in fast moving games.



Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GTG exceeds the most mainstream refresh rates requirements.




OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



USB Type-C Power Delivery 90W

Built-in a USB Type-C connection with 90W power delivery allows you to effortlessly connect to and charge your devices.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.



Gaming Intelligence APP

Customize and set the ultimate monitor modes with keyboard & mouse in a very easy way. Easily activate useful function in game and take advantages.

| | |
|---------------------------|---|
| 调节范围 (高度) | 0 ~ 100mm |
| PIP / PBP 分屏 | Yes |
| 窄边框设计 | Yes |
| 接口分辨率 | Display Port: 3440x1440 (Up to 240Hz) HDMI™: 3440x1440 (Up to 240Hz) Type C(DP alt.): 3440 x 1440 (Up to 240Hz) and 98W PD *Adobe RGB, DCI-P3 and sRGB follow CIE1976 Standard |
| 重量 | 8.8kg / 12.45kg 6.66kg (without stand) |
| Adobe RGB / DCI-P3 / sRGB | 97.8% / 99.3% / 139.1% |
| Warranty | 3 years (including panel burn-in) |

CONNECTIONS



1. AC in
2. 2x HDMI™ 2.1 (UWQHD@240Hz)
3. 1 x DP 1.4a
4. 1 x USB Type-C (98W)
5. 2 x USB 2.0 Type A
6. 1 x USB Type B
7. 1 x Headphone