



SPECIFICATIONS

屏幕尺寸	49"
显示区域 (mm)	1196.7 (H) x 339.2 (V)
曲面屏幕	Curve 1800R
面板类型	QD-OLED
最佳分辨率	5120 x 1440 (DQHD)
点距 (H x V)	0.233 (H) x 0.233 (V)
屏幕比例	32:9
屏幕亮度	SDR: 250 HDR: 450 (Typ.) (True Black 400 with 10% APL) 1000 (Typ.) (Peak 1000 with 3% APL)
对比度	1500000:1 (Typ.)
信号频率	30~390 KHz (H) / 48~240Hz (V)
激活范围	48~240Hz
刷新率	240Hz
响应时间	0.03ms (GtG)
动态刷新率技术	Adaptive-Sync
HDR支持	DisplayHDR True Black 400
显示接口	2x HDMI™ 2.1 (DQHD@240Hz) 1x DisplayPort 1.4a 1x Type-C (DP alt.) w/ 98W PD
USB 接口	2x USB 2.0 Type A 1x USB 2.0 Type B
音频接口	1 x Headphone-out
可视角度	178° (H) / 178° (V)
音频接口	1x Earphone out
动态对比度	N/A
包装尺寸 (W X D X H)	1333 x 286 x 493 mm (52.4 x 11.2 x 19.4 inch)
表面处理	Anti-Reflection
显示色彩	1.07B, 10 bits
防盗锁	Yes
VESA 支架	100 x 100 mm
电源适配器规格	Internal Power Board
电源输入	100~240V, 50/60Hz
调节角度 (倾斜)	-5° ~ 20°
调节角度 (旋转)	-30° ~ 30°
中心轴旋转	N/A
调节范围 (高度)	0 ~ 100mm

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming.

240Hz High Refresh Rate



Experience smooth gaming with a blazing-fast refresh rate, providing you with the upper hand in fast-moving games.



Fastest 0.03 Response time

Response time is much faster and smoother than conventional LCD displays. The response time is up to 0.03 ms GtG exceeds the most mainstream refresh rates requirements.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.




Gaming Intelligence APP

Customize and set the ultimate monitor modes with keyboard & mouse in a very easy way. Easily activate useful function in game and take advantages.



USB Type-C Power Delivery 98W

Built-in a USB Type-C connection with 98W power delivery allows you to effortlessly connect to and charge your devices.



Graphene film with Custom Heatsink

Graphene film and customized heatsink designs, the synergy between these two elements enables monitor to operate without an active cooling fan, achieving a fanless design. This ensures efficient and silent heat dispersion, further extending the panel's lifespan.

接口分辨率	HDMI™: 5120 x 1440 (Up to 240Hz) DisplayPort: 5120 x 1440 (Up to 240Hz) Type-C: 5120 x 1440 (Up to 240Hz) Support: HDMITM CEC, KVM, PIP/PBP
重量	10.6kg (23.3 lbs) / 16.4kg (36.1 lbs)
Adobe RGB / DCI-P3 / sRGB	98% / 99% / 146% (CIE1976 Standard)
Dimension with Stand (W x D x H)	1195 x 328 x 410 mm (47.0 x 12.9 x 16.1 inch)
Dimension without Stand (W x D x H)	1195 x 190 x 372 mm (47.0 x 7.48 x 14.64 inch)
配件	1x HDMI™ Cable (2.1), 1x DisplayPort Cable (1.4a), 1x USB Type-B to A Cable, 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw

CONNECTIONS



1. AC-in
2. 5-way Joystick Navigator
3. 2 x HDMI™ 2.1 (DQHD@240Hz)
4. Display Port 1.4a
5. USB Type-C PD 98W
6. 2 x USB 2.0 Type-A
7. USB 2.0 Type-B
8. Earphone out
9. Kensington lock