


SPECIFICATIONS

总线接口	PCI Express® Gen 4
型号名称	GeForce RTX™ 4070 Ti SUPRIM SE 12G
显示芯片	NVIDIA® GeForce RTX™ 4070 Ti
显存	12GB GDDR6X
显存位宽	192-bit
核心频率	Extreme Performance: 2625 MHz (MSI Center) Boost: 2610 MHz (GAMING & SILENT Mode)
显存速度	21 Gbps
最大屏幕输出数	4
G-SYNC® technology	Y
最大分辨率	7680x4320
输出接口	DisplayPort x 3(v1.4a) HDMI™ x 1 (supports 4K 120Hz HDR and 8K 60Hz HDR and Variable Refresh Rate (VRR) as specified in HDMI™ 2.1a)
HDCP 支持	Y
建议电源 (W)	750 W
供电接口	16-pin x 1
DirectX 版本支持	12 Ultimate
OpenGL 版本支持	4.6
显卡尺寸	338 x 142 x 73 mm
重量(显卡/包装盒)	2019g / 3224g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 3S

Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Copper Baseplate

The CNC machined nickel-plated copper base captures heat from the GPU and the memory then rapidly transfers it to Core Pipes.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Air Antegrade Fin

A section of V-shape heatsink and side-fins work to refocus air resistance at the passthrough.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.