



SPECIFICATIONS

总线接口	PCI Express® Gen 4
型号名称	GeForce RTX™ 4080 SUPER 16G SUPRIM X
显示芯片	NVIDIA® GeForce RTX™ 4080 SUPER
显存	16GB GDDR6X
显存位宽	256-bit
核心频率	Extreme Performance: 2655 MHz (MSI Center) Boost: 2640 MHz (GAMING & SILENT Mode)
显存速度	23 Gbps
最大屏幕输出数	4
G-SYNC® technology	Y
最大分辨率	7680 x 4320
输出接口	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI™ 2.1a)
HDCP 支持	Y
建议电源 (W)	850 W (Min. 750 W)
供电接口	16-pin x 1
DirectX 版本支持	12 Ultimate
OpenGL 版本支持	4.6
显卡尺寸	336 x 142 x 78 mm
重量(显卡/包装盒)	2372g / 3573g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TRI FROZR 3S

Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Vapor Chamber

The GPU and memory modules are covered with a Vapor Chamber which rapidly transfers heat to Core Pipes.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Wave Curved 3.0

Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.