




SPECIFICATIONS

总线接口	PCI Express® Gen 4
型号名称	GeForce RTX™ 4090 D 24G GAMING X SLIM
显示芯片	NVIDIA® GeForce RTX™ 4090 D
显存	24GB GDDR6X
显存位宽	384-bit
核心频率	Extreme Performance: 2535 MHz (MSI Center) Boost: 2520 MHz (GAMING & SILENT Mode)
显存速度	21 Gbps
最大屏幕输出数	4
G-SYNC® technology	Y
最大分辨率	7680 x 4320
输出接口	DisplayPort x 2 (v1.4a) HDMI™ x 2 (Supports 4K@120Hz HDR and 8K@60Hz HDR and Variable Refresh Rate (VRR) as specified in HDMI 2.1a)
HDCP 支持	Y
建议电源 (W)	850W
供电接口	16-pin x 1
DirectX 版本支持	12 Ultimate
OpenGL 版本支持	4.6
显卡尺寸	322 x 136 x 62 mm
重量(显卡/包装盒)	1777 g / 2477g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES




TRI FROZR 3

Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.



Copper Baseplate

Heat from the GPU and memory modules is captured by a copper baseplate and then rapidly transferred to Core Pipes.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Dual BIOS

Dual BIOS lets you set the priority to full performance in GAMING mode or low noise in SILENT mode.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.