




SPECIFICATIONS

总线接口	PCI Express® Gen 5 x16 (uses x8)
显示芯片	NVIDIA® GeForce RTX™ 5060 Ti
显存	16GB GDDR7
显存位宽	128-bit
核心频率	极致模式: 2587 MHz (MSI Center) Boost模式: 2572 MHz
显存速度	28 Gbps
最大屏幕输出数	4
G-SYNC® technology	Y
最大分辨率	7680 x 4320
输出接口	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP 支持	Y
建议电源 (W)	600W
供电接口	8-pin x1
DirectX 版本支持	12 Ultimate
OpenGL 版本支持	4.6
显卡尺寸	204 x 117 x 50 mm
重量(显卡/包装盒)	657g / 927g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.



STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.



Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.




Metal Backplate

A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.




Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Air Antegrade Fin

Fins with a V-shaped cutout are located at the airflow passthrough to improve flow efficiency.



Wave Curved 3.0

Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overlocking software in the world.