



## SPECIFICATIONS

总线接口	PCI Express® Gen 5 x16 (uses x8)
显示芯片	NVIDIA® GeForce RTX™
显存	16GB GDDR7
显存位宽	128-bit
核心频率	极致模式: 2707 MHz (MSI Center) Boost模式: 2692 MHz
显存速度	28 Gbps
最大屏幕输出数	4
G-SYNC® technology	Y
最大分辨率	7680 x 4320
输出接口	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP 支持	Y
建议电源 (W)	600W
供电接口	16-pin x 1
DirectX 版本支持	12 Ultimate
OpenGL 版本支持	4.6
显卡尺寸	337 x 140 x 61 mm
重量(显卡/包装盒)	1278 g / 2059 g

## CONNECTIONS



1. DisplayPort
2. HDMI™

## FEATURES



### TRI FROZR 4

Upgraded fans, airflow control, and thermal design deliver superior cooling and quieter operation.



### STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



### Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.




### Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.



### Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



### Wave Curved 4.0

Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.



### Air Antegrade Fin 2.0

The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.



### MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



### Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.