



SPECIFICATIONS

总线接口	PCI Express® Gen 5
显示芯片	NVIDIA® GeForce RTX™ 5070
显存	12GB GDDR7
显存位宽	192-bit
核心频率	极致模式: 2655 MHz (MSI Center) Boost模式: 2640 MHz
显存速度	28 Gbps
最大屏幕输出数	4
G-SYNC® technology	Y
最大分辨率	7680 x 4320
输出接口	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP 支持	Y
建议电源 (W)	650W
供电接口	16-pin x 1 (推荐使用ATX 3.1电源)
DirectX 版本支持	12 Ultimate
OpenGL 版本支持	4.6
显卡尺寸	337 x 140 x 61 mm
重量(显卡/包装盒)	1503 g / 3382 g

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



HYPER FROZR THERMAL DESIGN

An apex evolution of advanced thermal design that delivers unparalleled cooling and quiet operation.




STORMFORCE FAN

Seven fan blades, claw texturing, and a circular arc are designed for optimal airflow with minimal noise.



Advanced Vapor Chamber

Built-in Vapor Chamber swiftly transfers heat from the GPU and VRAM to the core pipe for optimal dissipation.




Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.




Filled Fins

Updated heat pipe pathing has allowed more space for additional heatsink fins.



Air Antegrade Fin 2.0

The fins feature a V-shaped cutout and a high-low design at the airflow passthrough to optimize flow efficiency.



Wave Curved 4.0

Precision-engineered wave edges with a high-low fin design enhance airflow and reduce turbulence.



Metal Backplate

A reinforcing metal backplate with airflow vents and thermal pads enhances cooling.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.